



HSR2

Premium regional and line-haul **steer** tyre

- ▶ Maximum life expectancy through customised tread geometry
- ▶ Even wear pattern under all load conditions through optimised contour, which ensures balanced pressure distribution in the ground contact patch
- ▶ Precise handling thanks to an advanced tread pattern and maximum grip in the wet with minimum wear through innovative tread compound for steer axes
- ▶ Reduced rolling resistance for better fuel economy



Technical data

Tyre Size	Load & Speed	Ply Rating	Type	Tread Depth (mm)	Overall Inflated Diameter (mm)	Section Inflated Width (mm)	Rec. Rim (inches)	Rolling Circ. (mm)	Maximum Axle Load @ Inflation Pressure			
									Single		Dual	
									KG	PSI (BAR)	KG	PSI (BAR)
255/70R22.5	140/137M	16	TL	14.2	944	265	7.5	2849	5000	116 (8.0)	9200	1163 (8.0)
295/80R22.5 [†]	152/148M	16	TL	15.8	1044	302	8.25	3185	7100	123 (8.5)	12600	123 (8.5)
385/65R22.5	160K	20	TL	15.3	1092	405	11.75	3267	9000	131 (9.0)	NA	NA

Applications



Refrigerated



General Cargo



General Cargo



Truck and Dog



B-Double



Car Hauler



Express Mail/Parcel Delivery



Tanker



Flat Bed



Intercity Coach