



Conti Hybrid HS3

Premium regional and line-haul **steer** tyre

- ▶ Narrowed groove widths result in increased pattern volume. This improves wear resistance, thereby guaranteeing high mileage
- ▶ An advanced contour shape ensures excellent pressure distribution, providing even wear characteristics for high mileage
- ▶ Wet performance pocket siping technology, with full-depth sipes, enhances water displacement and improves wet performance

Technical data

Tyre Size	Load & Speed	Ply Rating	Type	Tread Depth (mm)	Overall Inflated Diameter (mm)	Section Inflated Width (mm)	Rec. Rim (inches)	Rolling Circ. (mm)	Maximum Axle Load @ Inflation Pressure			
									Single		Dual	
									KG	PSI (BAR)	KG	PSI (BAR)
225/70R19.5	128/126N	14	TL	12.7	810	225	6	2545	3600	98 (6.75)	6800	98 (6.75)
265/70R19.5	140/138M	16	TL	12.9	881	272	7.5	2645	5000	116 (8.0)	9440	123 (8.5)
305/70R19.5	148/145M	18	TL	14.3	941	317	9	2815	6300	123 (8.5)	11600	123 (8.5)
315/70R22.5	154/150L	20	TL	14.8	1096	318	9	3280	7500	123 (8.5)	13400	123 (8.5)
385/55R22.5	160K	20	TL	14.3	1012	396	11.75	3059	9000	131 (9.0)	NA	NA
11R22.5*	148/145L	16	TL	16.5	1050	279	8.25	3200	6300	123 (8.5)	11600	123 (8.5)

Applications

